

SheerWeave 5000

Openness Factor:	± 3%, 5%, 7%; varies with style & color
UV Blockage:	± 97%, 95%, 93%; varies with style & color
Composition:	Polyester / Vinyl / Acrylic / Olefin (Variable)
Mesh Weight:	13.60 oz/yd ² - 16.10 oz/yd ² ; varies w/ style & color
Fabric Thickness:	0.036" - 0.052"; varies w/ style & color
Recommended Use:	Interior / Exterior
Standard Roll Widths:	74" & 98"

Additional SheerWeave 5000 Specifications:

Environmental Certification:	GREENGUARD Indoor Air Quality Certified (LEED™) GREENGUARD for Children and Schools Certified
Fire Classification:	California Technical Bulletin 117 Sect E. Part 1, NFPA 101 (Class A Rating), and UBC (Class 1) *For Q49, Q50, Q51: NFPA 701-2004 TM#1 (Small Scale)
Bacteria & Fungal Resistance:	ASTM E 2180, ASTM G 21, & ASTM G22; includes Microban antimicrobial additives
Lead Free:	RoHS / Directive 2002/95/EC, US Consumer Product Safety Commission Section 101, ANSI/WCMA A100. 1-2007 for lead content and REACH (EC 1907/2006) compliant